

EXHIBIT 5

BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number
WO 2004/028318 A1

(51) International Patent Classification: A47J 31/40, 31/44

(74) Agents: SCHOUTEN, Marcas, M.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number:
PCT/IB2003/004085

(81) Designated States (national): AR, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LI, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:
17 September 2003 (17.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02079000.2 27 September 2002 (27.09.2002) EP

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


(75) Inventor/Applicant (for US only): BRUINSMA, Rodin, E. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(i)) for the following designations AR, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH,

[Continued on next page]

(54) Title: APPARATUS FOR PREPARING COFFEE



(57) Abstract: An apparatus for preparing coffee includes a holder (4) provided with an access opening (24) for placing a pouch filled with a product to be extracted into the holder (4); a cover (34) for closing and releasing the access opening (24); clamping means (70) for pressing the holder (4) and cover (34) towards each other when the cover (34) closes off the access opening (24) of the holder (4); and closing means (80) for retaining the cover (34) and the clamping means (70) in position when the cover (34) closes off the access opening (24) of the holder (4). The closing means (80) are mechanically coupled to the clamping means (70) for bringing the clamping means (70) from a non-clamping condition into a clamping condition by manually operating the closing means (80) from a first defined position to a second defined position.

WO 2004/028318 A1

CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patents (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patents (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE,

DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patents (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2004/028318

PCT/IB2003/004085

1

Apparatus for preparing coffee

The invention relates to an apparatus for preparing coffee, comprising a holder provided with an access opening for placing a product to be extracted into said holder; a cover for closing and releasing the access opening; clamping means for pressing the holder and cover towards each other when the cover closes off the access opening of the holder and closing means for retaining the cover and the clamping means in position when the cover closes off the access opening of the holder.

Such an apparatus is known from EP 0 904 718. In this known apparatus the holder is mounted in a first housing part and the cover is spring adjustably mounted in a second housing part. To close the apparatus, the second housing part is pivoted towards the first housing part, whereupon the spring will adjust the orientation of the cover so that it can properly engage the holder. Due to this adjustment, clamping means at the inner side of the second housing part engage clamping means at the outer side of the cover, thus establishing a clamping force which presses the cover onto the holder. Subsequently, a clip on the second housing part can be hooked behind a protrusion of the first housing part, to retain the cover and clamping means in the closed position.

A disadvantage of this known apparatus is that the spring and clamping means allow the cover to become misaligned during closure, without a user noticing. The misalignment can for instance be prompted due to a pouch or other filter structure or coffee granulate being misplaced and getting caught between the edges of the cover and the holder or due to too many pouches having been placed in the holder. Due to such misalignment no proper seal will be attained between the holder and cover and consequently, in use, the pressure in the holder will be too low, affecting the quality of the brew.

25

It is an object of the invention to provide an apparatus of the above-described type, wherein the risk of operation with the cover not properly aligned is reduced.

WO 2004/028318

PCT/IB2003/004085

2

To that end, in an apparatus according to the invention the closing means are mechanically coupled to the clamping means for bringing the clamping means from a non-clamping condition into a clamping condition by manually operating the closing means from a first defined position to a second defined position. Such a configuration offers the advantage that a user obtains immediate tactile and visual feedback regarding the state of the clamping means, and hence the state of the cover, from operating the closing means. If, for instance, a force for operating the closing means is considerably lower or higher than usual, this will signal the user that the cover is positioned incorrectly, or at least that something is not working properly. The user may then take appropriate action to remedy the cause.

Furthermore, as long as the closing means have not reached one of their two defined end positions, the user is informed that the clamping means have not reached their end position either and the cover is not, or not yet, properly engaged.

The clamping means can for instance comprise one or more cams and mating recesses, which can be brought into and out of engagement with each other by operating the closing means. Preferably the configuration of the cams and recesses is such that they can only be engaged when the cover is properly closing off the holder. Thus, if for whatever reason the cover is not properly aligned, the closing means will not be operable to the closed end position, thereby sending a clear message to the user, both tactile and visual, that something is the matter.

Preferably the cams are at least partly wedge-shaped. This offers the advantage that the clamping force can be gradually built up, while advancing the cams in the recesses, thus facilitating the operation of the closing means.

According to an advantageous embodiment of an apparatus according to the invention, part of the clamping means is statically mounted in a first housing part to which the holder is connected, whereas the mating clamping means are movably mounted in a second housing part to which the cover is connected. Preferably, said movable clamping means are mounted on a single slider, which slider is movably connected to the second housing part. In that way, by displacing, e.g. rotating and/or translating the slider, all movable clamping means can be simultaneously brought into engagement with the static clamping means. Since only a single slider will have to be operated, the closing means can be of a simple, robust construction and will be easy to operate. Furthermore, the construction will have a high sensitivity to detecting misalignment of the cover, for if only one pair of co-operating clamping means cannot be properly engaged, the complete slider will not attain its

WO 2004/028318

PCT/IB2003/004085

3

engaged position, which again will be communicated to the user by the position of the closing means.

The cover can either be connected to the slider and, together with the slider and the clamping means, be slid into the closing position, or it can be connected to the second housing part, separately from the slider. In the latter case, the cover can be clamped onto the holder by means of the slider pressing directly onto the cover, or indirectly, by means of the second housing part, which itself is being clamped onto the first housing part.

In a further advantageous embodiment, the clamping means are spaced evenly along the access opening of the holder, at least in the clamped condition. As a result, the clamping force will be evenly distributed over the cover, in particularly around its periphery, resulting in a good, reliable seal. The clamping means can for instance be arranged around the access opening in a triangle, preferably an equilateral triangle. If so, the widest part of the triangle, that is the base thereof, preferably faces a front side of the apparatus so that the accessibility of the holder is not hampered.

According to yet a further preferred embodiment, the closing means for operating the clamping means include a toggle joint lever. By applying such a toggle joint lever the force needed for operating the slider and bringing the clamping means into engagement can be kept relatively low. Although the operating force will be low, this will still contain sufficient information regarding the state of the clamping means and cover. Hence, ease of operation can be increased, without compromising the feedback function of the closing means.

In a highly preferred embodiment, the closing means furthermore comprise a spring, which helps return the closing means to either one of its two defined end positions, thereby communicating to the user whether the closure of the holder has been successful or not. Preferably, the design of the toggle joint lever and spring action is chosen such that the movement of the closing means between said two defined positions corresponds to a natural sense for opening and closing the apparatus.

The above and other advantageous embodiments of the invention are set forth in the dependent claims.

To explain the invention, exemplary embodiments thereof will hereinafter be described with reference to the accompanying drawings, wherein:

WO 2004/028318

PCT/IB2003/004685

4

Fig. 1 shows a cross section of the apparatus according to the invention, in the closed condition;

Fig. 2 shows a cross section of the apparatus according to Fig. 1, in the partly opened condition;

5 Fig. 3 shows a cross section of the apparatus according to Fig. 1, in the completely opened condition;

Fig. 4 shows schematically, in cross section, in four subsequent steps the working of the closing and clamping means according to the invention, during opening and closing of an apparatus according to Fig. 1;

10 Fig. 5 shows in a plan view a preferred embodiment of a slider according to the invention; and

Fig. 6 shows in an exploded and assembled view the various parts of a closing and clamping configuration according to an embodiment of the present invention.

15

In this description, the same or corresponding parts have the same or corresponding reference numerals.

20 Figs. 1-3 show an apparatus 1 for preparing coffee, comprising a first housing part 2, in which a holder 4 has been mounted and a second housing part 44, in which a cover 34 has been mounted.

The holder 4 is of a cup-shaped design, comprising a bottom 16 and an upright, circumferential sidewall 18, connected to the bottom 16. At its upper end, the holder 4 is provided with an access opening 24, for receiving a product to be extracted, for instance a pouch, made of filter material and filled with for instance ground coffee. Provided in the
25 bottom 16 of the holder 4 is at least one outflow opening (not visible in the Figures) for discharging extracted liquid.

The cover 34 is designed to accurately close off the access opening 24 of the holder 4. At its upper side, an inflow opening is provided through which water is passed into the holder 4, and onto the product to be extracted. To that end, the inflow opening is
30 connected to a hot water supply 42 (not shown), via a liquid duct 40. Furthermore, the side of the cover 34 facing the holder 4 can be equipped with a sealing ring, which in use co-operates with the holder 4 to ensure a proper liquid seal between the holder 4 and the cover 34.

The second housing part 44 is adjacent one end connected to the first housing

WO 2004/028318

PCT/IB2003/004085

5

opening 24 is closed off by the cover 34 (as illustrated in Figs. 1 and 2) and a second position in which the access opening 24 of the holder 4 is cleared (as shown in Fig. 3).

The apparatus 1 furthermore comprises clamping means 70 for pressing the cover 34 against the holder 4 when it closes off the access opening 24 of the holder 4, and closing means 80 for maintaining the cover 34 and the clamping means 70 in the
5 aforementioned position.

As is best seen in Figs. 2, 4 and 5, the clamping means 70 comprise three sets of recesses 72 and mating cams 74. The recesses 72 are provided in the first housing part 2, spaced in a triangle around the access opening 24 of the holder 4. The cams 74 are provided
10 on a substantially triangular slider 75 (see Figs. 4 and 5), adjacent the three corners thereof. The slider 75 is movably mounted in the second housing part 44, and can be operated by the closing means 80, in a way to be described in more detail below, between a first and a second position, in which the cams 74 are respectively in and out of engagement with the recesses
12 72.

Thanks to the triangular configuration the clamping means 70 are spaced at
15 more or less regular angles along the periphery of the access opening 24. Consequently, the clamping force will be evenly distributed along the edge of the cover 34, resulting in a reliable seal. Of course, more cams and mating recesses can be applied within the scope of the invention. These cams and recesses may be spaced differently around the access opening.
20 Also, the position of the cams and recesses can be interchanged, that is the cams 74 can be mounted in the first housing part 2, whereas the recesses 72 can be provided in the slider 75.

In case the triangular configuration is applied, the triangle is preferably oriented in such a way that the widest part thereof, that is base B, faces the front side of the apparatus 1 via which products are placed into or removed from the holder 4, as indicated by
25 arrow A in Fig. 5. In this way, the accessibility of the holder 4 need hardly be affected.

Preferably, the cams 74 are of a wedge-shaped design (as illustrated in Figs. 1 and 2). This facilitates introducing the cams 74 into the recesses 72 and enables the clamping force to be built up gradually while the cams 74 enter the recesses 72. Of course, other shapes are possible and understood to fall within the scope of protection.

30 The closing means 80 for operating the slider 75 comprise a lever 82, a push rod 84, and a spring 86. The lever 82 has an angular shape and, near its angle, is rotatably connected to the second housing part 44, for rotation around a first rotation axis 90. A first end 82A of the lever 82 extends from the rotation axis 90 to outside the second housing part 44, through an opening 45 (see Fig. 6). The second end 82B of the lever 82 is

WO 2004/028318

PCT/DE2003/004085

6

the push rod 84, i.e. to a first end 88 thereof, for rotation around a second rotation axis 92. This second rotation axis 92 extends substantially parallel to the first rotation axis 90. The push rod 84 is connected, near its other end 89, to the slider 75, more specifically to two mounting brackets 78 extending upward from the slider 75, for rotation around a third rotation axis 94. This third rotation axis 94 extends substantially parallel to the first and the second rotation axis 90, 92. In the push rod 84 a slot 87 is provided, which extends from the second end 89, between the mounting brackets 78, in the longitudinal direction. This slot 87 provides a passage for the liquid duct 40 of the cover 34, which extends at least partially below the slider 75 and can be connected either to said slider 75 or to the second housing part 44.

The lever 82 and push rod 84 together form a toggle joint lever assembly 85, with which the slider 75 can be operated from a non-clamping to a clamping position, with a relatively low operating force. The closing means 80 furthermore comprise a spring 86, which at one end is connected to the slider 75 or the push rod 84, near the third rotation axis 94, and at an opposite end is connected to the second housing part 44. The spring 86 turns the toggle joint into a snap mechanism, and helps a user operate the lever 82 between its defined end positions I, II.

The operation of the closing and clamping means 80, 70 is as follows. In a closed position, illustrated in Fig. 4A, the cover 34 closes off the opening 24 and is clamped onto the holder 4 by means of the slider 75, which is engaged into the recesses 72 by means of the cams 74. In this position, the spring 86 is slightly compressed and exerts a force on the push rod 84, which tends to rotate the lever 82 counterclockwise, to a first defined end position I, in which the second end 82B of the lever 82 abuts the inner side of the second housing part 44 and the first end of the lever 82A extends downward, against part of the outer side of the second housing part 44 (see Fig. 4A). A user can see from this first lever position I that the cover 34 is properly closed.

To open the apparatus 1 and lift the cover 34 from the holder 4, the first end 82A of the lever 82 is rotated clockwise, around the first rotation axis 90 in the direction of arrow C (see Fig. 4B). Consequently, the push rod 84 is rotated counterclockwise around the third rotation axis 94, against the force of the spring 86. The spring 86 is compressed until the lever 82 passes the point where the second end 82B and the push rod 84 are aligned. The spring 86 then recovers from compression and expands, thereby pushing the slider 75 sideward and disengaging the cams 74 from the recesses 72. Simultaneously, the second end

WO 2004/028318

PCT/IB2003/004085

7

82A is rotated upward, away from the second housing part 44 to a second defined end position II (see fig. 4C). In this position the push rod 84 extends about parallel to the slider 75 and the spring 86 is not compressed. In this position the upward extending lever 82 signals to the user that the cover 34 is now unclamped. For gaining access to the holder 4, the user may proceed by rotating the second housing part 44 around its rotation axis 50, away from the first housing part 2, thus lifting the cover 34 from the holder 4 (as shown in Fig. 4D). After placing a product to be extracted into the holder 4, the apparatus 1 can be closed by going through the above-described steps in reversed order. Thus, the lever end 82A is rotated downwards, against the spring force, till the spring 86 snaps and rotates the lever 82 further till the second lever end 82B abuts the inner side of the second housing part 44 and locks the lever 82 and slider 75 against further movement.

The closing and clamping means 80, 70 as described offer several advantages. For instance, because the clamping means 70 are brought into a clamping condition by the user himself instead of by a spring, the user obtains immediate feedback on the status of the cover 34 from the force needed to operate the closing means. Preferably the clamping means 72, 74 are dimensioned such that if the cover 34 is near its closed position but does not properly seal the holder 4, the cams 74 cannot be brought into engagement with the recesses 72. The lever 82 will then retain its second end position II or at least not reach its first end position I, thus indicating to the user that no proper closure could be achieved. The user may then take appropriate action to remedy the cause, for instance by reopening the second housing part 44 and rearranging the pouch.

Furthermore, the toggle joint design of the closing means allows the clamping means to be operated with relatively little effort, without undoing the feedback function of the closing means. Thanks to the snap mechanism the first lever end 82A will at all times be returned to one of its two defined end positions I, II, to provide the user with reliable visual information about the state of the cover 34. Preferably, the design of the snap mechanism is such that the movement between the first and second position of the lever corresponds to a natural movement for opening or closing the apparatus 1.

Although not shown, the slider 75 and second housing part 44 can be equipped with co-operating guiding means, for guiding the slider 75 during its movement between the clamping and non-clamping position and support the slider 75 in retaining a preferred orientation with regard to the access opening 24.

The invention is not in any way limited to the embodiments described

WO 2004/028318

PCT/IB2003/004085

8

For instance, the slider can be designed to surround the cover or overlap the cover, at least partly, in the clamped condition. Also, the cover and the slider can be connected to the second housing part jointly or separately. The slider and the closing means can be arranged for rotating the slider around a rotation axis extending substantially

5 perpendicularly to the plane of the slider or extending substantially parallel to said plane. Furthermore, the engaging movement of the slider can be a combination of a rotational and a linear movement. The cams and recesses may differ in number, shape and position from the ones shown in the accompanying drawing.

Such variants are understood to fall within the scope of the invention.

WO 2004/028318

PCT/TR2003/004085

9

CLAIMS:

1. An apparatus for preparing coffee, comprising
 - a holder (4) provided with an access opening (24) for placing a product to be extracted into said holder (4);
 - a cover (34) for closing and releasing the access opening (24);
 - 5 - clamping means (70) for pressing the holder (4) and cover (34) towards each other when the cover (34) closes off the access opening (24) of the holder (4); and
 - closing means (80) for retaining the cover (34) and the clamping means (70) in position when the cover (34) closes off the access opening (24) of the holder (4), characterized in that the closing means (80) are mechanically coupled to the clamping means
 - 10 (70) for bringing the clamping means (70) from a non-clamping condition into a clamping condition by manually operating the closing means (80) from a first defined position to a second defined position.
2. An apparatus according to claim 1, wherein the clamping means (70) comprise
 - 15 at least one recess (72) and at least one mating cam (74), which can be brought into and out of engagement with each other by operating the closing means (80) between the first and the second position.
3. An apparatus according to claim 2, wherein the or each cam and the mating
 - 20 recess (72) are located and dimensioned in such way that the cam can only engage the recess (72) when the cover (34) closes off the holder (4) properly.
4. An apparatus according to claim 2 or 3, wherein the or each cam and the
 - 25 recess (72) are wedge-shaped, so that a clamping force can be gradually built up.
5. An apparatus according to any one of the preceding claims, wherein the clamping means (70) comprise a series of recesses (72) and a series of mating cams (74), wherein one of these series is statically mounted in a first housing part (2) to which the

WO 2004/028318

PCT/IB2003/004085

10

holder (4) is connected, and the other series is movably mounted in a second housing part (44) to which the cover (34) is connected.

6. An apparatus according to claim 5, wherein the clamping means (70) are evenly spaced along the periphery of the access opening (24) of the holder (4), at least in the clamped condition.

7. An apparatus according to claim 5 or 6, wherein the clamping means (70) are arranged in a triangle around the access opening (24) of the holder (4), wherein a base of the triangle faces a front side of the apparatus via which the holder (4) is accessible when the apparatus is opened.

8. An apparatus according to any one of claims 5-7, wherein the series of movably mounted clamping means (70) is mounted on a slider (75), which slider is movably connected to the second housing part (44) and mechanically coupled to the closing means (80).

9. An apparatus according to claim 8, wherein the slider is translatably mounted in the second housing part (44).

10. An apparatus according to claim 8 or 9, wherein the slider (75) is rotatably mounted in the second housing part (44).

11. An apparatus according to any one of claims 8-10, wherein the cover (34) is connected to the slider (75), and operated together with said slider (75) and clamping means (70) by the closing means (80).

12. An apparatus according to any one of the claims 8-11, wherein the closing means (80) comprise a toggle joint lever assembly (85), including an angular shaped lever (82A) and a push rod (84), the lever being connected to the second housing part (44), for rotation around a first rotation axis, the lever furthermore being connected near one end to the push rod, for rotation around a second rotation axis, the push rod (84) being with its other end connected to the slider (75), for rotation around a third rotation axis, such that by operating

WO 2004/028318

PCT/IB2003/004085

11

is displaced between a first position wherein the clamping means (70) are not engaged and a second position wherein the clamping means (70) are engaged.

13. An apparatus according to claim 12, wherein the closing means (80) comprise
S a spring (86), which returns the lever to one of its two positions.

14. An apparatus according to claim 13, wherein the spring (86) extends between the second housing part (44) and the slider (75) or push rod (84), near the third rotation axis, for forming an overcenter snap link.

WO 2004/028318

PCT/IB2003/004095

1/6




FIG. 1

WO 2004/028318

PCT/TB2003/004085

2/6




FIG. 2

WO 2004/028318

PCT/IB2003/004085

3/6




FIG. 3

WO 2004/028318

PCT/IB2003/004085

4/6




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D

WO 2004/028318

PCT/IB2003/004085

5/6




FIG. 5

WO 2004/028318

PCT/TB2003/004085

6/6




FIG. 6

INTERNATIONAL SEARCH REPORT

PCT/IB 03/04085

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A47J31/40 A47J31/44

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 A47J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 08990 A (FISCHER DANIEL ;EUGSTER FRISMA8 AG (CH)) 28 March 1996 (1996-03-28) page 8, line 14 - line 19 figures 4-6	1-3,5,8, 10,11
X	WO 01 15582 A (KRAAN DIEDERIK ;LEE DE NV SARA (NL)) 8 March 2001 (2001-03-08) page 6, line 25 -page 7, line 3 page 7, line 16 - line 20 page 8, line 17 - line 24 page 9, line 18 - line 29 figures 1,5A,5B	1,2

-/-

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application believed to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

18 December 2003

Date of mailing of the international search report

30/12/2003

Name and mailing address of the ISA

European Patent Office, P.O. Box 1280, 6000 Leuven 2

Authorized officer

INTERNATIONAL SEARCH REPORT

PCT/IB 03/04085

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 904 718 A (LEE DE NV SARA) 31 March 1999 (1999-03-31) cited in the application column 5, line 31 - line 34 column 6, line 25 - line 32 figures 1, 5A, 5B	1
X	US 5 649 472 A (PLEISCH JEAN-PIERRE ET AL) 22 July 1997 (1997-07-22) column 12, line 25 - line 39 figures 11, 12	1

INTERNATIONAL SEARCH REPORT

PCT/IB 03/04085

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9608990	A	28-03-1996	DE 9415374 U1	02-03-1995
			WO 9608990 A1	28-03-1996
			AU 3566095 A	09-04-1996
			DE 59505973 D1	24-06-1999
			EP 0730425 A1	11-09-1996
			US 5794519 A	18-08-1998
			ES 2134493 T3	01-10-1999
WO 0115582	A	08-03-2001	NL 1012847 C2	20-02-2001
			AU 6482800 A	26-03-2001
			EP 1209997 A1	05-06-2002
			JP 2003508103 T	04-03-2003
			WO 0115582 A1	08-03-2001
EP 0904718	A	31-03-1999	NL 1007169 C2	31-03-1999
			AT 237270 T	15-05-2003
			AU 752303 B2	12-09-2002
			AU 8713398 A	22-04-1999
			DE 69813428 D1	22-05-2003
			EP 0904718 A1	31-03-1999
			JP 11206573 A	03-08-1999
			US 6009792 A	04-01-2000
US 5649472	A	22-07-1997	AU 671650 B2	05-09-1996
			AU 4414893 A	14-02-1994
			BR 9305586 A	02-05-1995
			DE 69321209 D1	29-10-1998
			DE 69321209 T2	18-02-1999
			DK 604615 T3	14-06-1999
			EP 0604615 A1	06-07-1994
			FI 941256 A	17-03-1994
			HK 1012536 A1	12-05-2000
			JP 3315121 B2	19-08-2002
			JP 6511182 T	15-12-1994
			NO 940248 A	03-02-1994
			AT 171352 T	15-10-1998
			CA 2111990 A1	03-02-1994
			WO 9402059 A1	03-02-1994
			EP 0870457 A1	14-10-1998
			ES 2122026 T3	16-12-1998
			NZ 253663 A	28-05-1996
			US 5826492 A	27-10-1998
			US 5762987 A	09-06-1998

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.